



Autopilot to Success



Why EASY2 Change?

The new EASY2 Change assistant supports the machine operator during every necessary step of a product change-over. Thanks to an intuitive HMI, the operator maintains full transparency and control throughout the change-over. Innovative technology detects the bubble stability, ensuring reproducible high film quality.

- Overview and direct guide to pending tasks
- Integration of fully automated air ring ARCTIS"
- Integration of proven automation features from systems like EASY Change, EASY Wind, TURBOCLEAN, Profile Booster, ...

Compared to an experienced operator, the number of necessary klicks for a product change is reduced by more than 70% and the time needed is cut by over half – and all that with a certainty that all parameters are set correctly to ensure good production.

Your advantages

- Operator guidance for error prevention
- Integrated bubble shape and frostline check
- Automatic setting of all components, including air ring

had sharings		1122 Page 4.1.1	• ==	1736(7020 👄				24.08.22 11
	•°	E.	r e	L.	•	Ŷ	1	Ť
	°	. °	с АШТС	L.°	•	f		-11
		0				Selport / actual devia 41 % Prost line deviation 200 m Witble value 2 m		
Winder Winder A	•		Contendar O Mildh controllar O Thickness controllar	Formal Web webs Distances		Default 1.400 mm 76.0 pm	Quality @ Film profile @ Hinds width	Dustile 10
151.00			 Profile measurement Profile caritral 	Throughput Throughput Throughput Throughput	ana agin	553 kg/h	Trengingent Ruby boundary visite	



